

| Contemporary

# Luminaire Trident.

With the idea of perpetuating the Atelier lighting, and giving it a refined and contemporary look.

✔ The project meets the requirements of the Order of 27 December 2018 on the prevention, reduction and limitation of light pollution.



CHRYSA LIS



## ▼ MATERIALS AND FINISHES

- Class II luminaire
- Base in cylindrical aluminum casting
- 3 screwed straight arms in extruded aluminum, sections 25x20x30mm, height 520mm
- Top plate in spun aluminum Ø705mm, with 30mm edge.
- Passage of the electrical cable inside one of the arms.
- Sealed, screen-printed LOLITA bowl:
  - in IK08 flat glass, as standard
  - in IK10 polycarbonate, on request
- Aluminum strips between PCBs to reduce glare
- RAL / Akzo Nobel powder coating of your choice, seaside option on request

## ▼ EQUIPMENT

- LOLITA COMPACT OPTICAL BLOCK:
  - PMMA optical lenses
  - Aluminum PCB (2 PCBs maximum)
  - Optics: Road (R), Semi-urban (SU), Urban (U), Square (P), Cycle path (PCY), Pedestrian crossing, Architectural.
  - Color temperatures: 3000K, 2700K, 2200K, 1800K (4000K, on request)
  - Coexistence of 2 optional color temperatures\*.
  - Cable gland
  - Pre-wired HO7 RN-F flexible (Length depending on equipment)
  - ULR < 1%, ULR < 4% (in situ), CIE flux 3 code > 95%
- EQUIPMENT remote at the base of the pole :
  - IP66 waterproofing
  - Optional antenna socket (Fixing depending on configuration)
  - Driver Light prog, Driver Full prog (With DALI output on request). SR or D4I driver and socket, optional
  - \*Additional driver for mixed temperature option
- ELECTRICAL PROTECTION:
  - 10kV surge protector on request
  - Varistor on request
- All our components are ENEC certified

## ▼ FIXINGS

- **STANDARD :**
  - Cover assembly for Ø60mm top or suspended

## ▼ DIMENSIONS

